

# Triumph®

by IDEAL


## → TRIUMPH 3915

SEMI-AUTOMATIC CUTTER · electric blade drive · patented, lever-activated, fast-action clamp · spindle-guided back gauge with calibrated crank · optical cutting line · side guide with measuring scale · solid steel blade carrier · optional stand (shown) or cabinet · **SAFETY FEATURES:** external blade depth adjustment · two-hand operation · transparent safety guards on front and rear tables · automatic blade return from any position · disc brake for instant blade stop · safety lock with key and main switch

Dimensions (D x W x H): 27 ½ x 20 ¾ x 19 inches (41 H with stand, 44 H with cabinet),  
Shipping weight: 180 lbs. (206 with stand, 272 with cabinet)



### FAST-ACTION CLAMP



Throw the lever on the fast-action clamp to tighten, then cut.

### CALIBRATED CRANK



A calibrated hand crank ensures exact positioning of back gauge.

### → TRIUMPH 3915

Cutting width	15 ¾"
Cutting height	1 ½"
Narrow cut	1 ⅜"
Cutting length behind blade	15 ½"
Table length in front of blade	8"
Motor	.5 hp
Power supply	115 V, 60 Hz

Dealer:

**MBM**  
CORPORATION

3134 Industry Drive  
North Charleston, South Carolina 29418  
800-223-2508, fax: 843-552-2974  
[www.mbmcorp.com](http://www.mbmcorp.com)

**IDEAL.MBM**  
CORPORATION

1 Regan Road, unit 12  
Brampton, Ontario L7A 1B8  
800-387-2528, fax: 905-840-1114  
[www.ideal-mbm.com](http://www.ideal-mbm.com)